

Franklin Electric Motors

- Reliable motors
- Ideal for 4" bore hole pumps
- Single or three phase motors available



Franklin Electric



MOTOR ELECTRICAL DATA

Code	Current Type	kW	Hp	Amps	RPM	Capacitor (μF)	Weight (kg)
PUFRK005M	Single	0.37	0.55	3	2850	16	7.2
PUFRK005MI	Single PSC	0.37	0.55	4.1	2850	Inbuilt	7.2
PUFRK007MI	Single PSC	0.55	0.75	6.5	2850	Inbuilt	7.2

PUFRK005T	Three	0.37	0.55	1.1	2850	-	6.3
PUFRK007T	Three	0.55	0.75	1.6	2850	-	7.2
PUFRK010T	Three	0.75	1	2.1	2850	-	8
PUFRK015T	Three	1.1	1.5	3	2850	-	9.3
PUFRK020T	Three	1.5	2	4	2850	-	10.3
PUFRK030T	Three	2.2	3	5.9	2850	-	12
PUFRK040T	Three	3	4	7.8	2850	-	14.3
PUFRK055T	Three	4	5.5	10	2850	-	21.8
PUFRK075T	Three	5.5	8	13.7	2850	-	28.7

MOTOR DIMENSIONS

Code	kW	W	L	Weight (kg)
PUFRK005M	0.37	96	242	7.3
PUFRK005MI	0.37	96	242	7.2
PUFRK005T	0.37	96	242	6.3
PUFRK007MI	0.55	96	271	7.2
PUFRK007T	0.55	96	271	7.2
PUFRK010T	0.75	96	251	8
PUFRK015T	1.1	96	297	9.3
PUFRK020T	1.5	96	321	10.3
PUFRK030T	2.2	96	353	12
PUFRK040T	3	96	408	14.3
PUFRK055T	4	96		21.8
PUFRK075T	5.5	96		28.7

